

## Datasheet TEMP



TEMP friction-welded dual metal bearings are fundamental parts used in industrial machinery. They are manufactured by friction-melt welding together dual metal roller bearings and dual metal discs. This product utilises a copper alloy as the sliding material that comes into contact with the shaft, providing good lubrication and protective capabilities for the shaft and the shaft shoulders. The base metal is steel, which allows for higher load-bearing capability and lower material costs.

### Application

Suitable for medium/low-speed and high-load rotation, swing and other uses.

### Material

Steel and copper.

### Availability

	Value	Unit
Inside diameter	on request	
Outside diameter	on request	
Flange diameter	on request	
Flange height	on request	
Total length	on request	

## TEMP - Specifications

### Physical properties

	Test standard	Value	Unit
--	---------------	-------	------

### Mechanical properties

	Test standard	Value	Unit
Compressive strength static		on request	
Module of elasticity - Youngs modulus		on request	
Tensile strength		on request	
Shear strength		on request	
Impact strength		on request	
Hardness		on request	
Dynamic load capacity		65	MPa

### Thermal properties

	Test standard	Value	Unit
Min. working temperature		on request	
Max. working temperature		260	°C
Intermittent working temperature		on request	

### Friction properties

	Test standard	Value	Unit
Coefficient of friction dynamic		on request	
Max. sliding speed		on request	
Max. Pv-load dry		on request	
Max. Pv-load oil lubricated		on request	
Max. Pv-load on regular greased		on request	

### Electrical properties

	Test standard	Value	Unit
--	---------------	-------	------